

E30TURBOEXIR

Turbo HD EXIR Turret Camera



▶ Camera

Image Sensor	3MP CMOS Image Sensor
Effective Pixels	2052(H)*1536(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Speed	1/25(1/30)s to 1/50,000s
Lens	2.8 mm Angle of View: 84°(2.8 mm)
Lens Mount	M12
Day & Night	ICR
Angle Adjustment	Pan: 0° - 360°, Tilt: 0° - 75°, Rotate: 0° - 360°
Synchronization	Internal Synchronization
Video Frame Rate	1920x1536@18 fps
HD Video Output	1 Analog HD output

S/N Ratio More than 62dB

▶ General

Operating Conditions	-40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)
Power Supply	12 VDC±15%
Power Consumption	Max. 5W
Protection Level	IP66
IR Range	10 to 20m
Communication	Up the coax (TVI output)
Dimensions	91 mm×82.6 mm×68.3 mm (3.58"×3.25"×2.69")
Weight	Approx. 350g (0.77lb)

▶ Menu

AGC	Support
D/N Mode	Color/BW/SMART
White Balance	ATW / MWB
BLC	Support
Functions	Digital noise reduction, Mirror, SMART IR

