

B8TURBOVZ / W

epcom®

HD 1080p Turbo HD Bullet Camera



B8TURBOVZ

B8TURBOVZW

▶ Camera

Image Sensor	2MP CMOS Image Sensor
Signal System	PAL / NTSC
Effective Pixels	1928 (H)*1088 (V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25 (1/30)s to 1/50,000 s
Lens	Motorized VF lens; 2.8 - 12 mm @ F1.2
Lens Mount	φ14
Day & Night	ICR
Angle Adjustment	Pan: 0° - 360°; Tilt:0° - 90°; Rotate: 0° - 360°
Synchronization	Internal synchronization
WDR	120 dB
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
S / N Ratio	>62dB

▶ General

Operating Conditions	-40°C-60°C(-40°F-140°F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC ±15%
Power Consumption	Max. 5W; -A: Max. 6W
Weather Proof Ratings	IP66
IR Range	Up to 40 m
Communication	Up the coax, Protocol: (TVI output)
Dimensions	92 × 84.8 × 269.6mm(3.62" × 3.34" × 3.34")
Weight	Approx. 900g (1.98lb)

▶ Menu

AGC	High/Medium/Low/Off
D/N Mode	Color/BW/SMART
White Balance	ATW/ MWB
BLC	Support
Functions	Wide Dynamic Range, Digital noise reduction, Mirror, SMART IR

▶ Key Features

2 Megapixel high-performance CMOS
Analog HD output, up to 1080P resolution
True Day/Night
2.8-12mm motorized vari-focal lens
OSD menu, DNR, Smart IR
True WDR, up to 120 dB
EXIR technology, up to 40 m IR distance
IP66 weatherproof
Up the Coax (HIKVISION-C)

TURBOHD ▶ series