

LB7TURBOVX/W

HD720P IR BULLET CAMERA



▶ Camera

Image Sensor	1 MP CMOS image sensor
Signal System	PAL / NTSC
Effective Pixels	1296(H) × 732(V)
Min. Illumination	0.1 Lux@(F1.2,AGC ON),0 Lux with IR
Shutter Time	1/25 (1/30)s to 1/50,000 s
Lens	2.8 - 12 mm @ F1.4 Angle of view: 71.78° - 23.42°
Lens Mount	φ14
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	720p@25fps/720p@30fps
HD Video Output	1 Analog HD output
S/N Ratio	>62dB



▶ General

Operating Conditions	-40 °C – 60 °C (-40 °F – 140 °F), Humidity 90% or less (non-condensing)
Power Supply	12 VDC± 15%
Power Consumption	Max. 4W
Protection Level	IP66
IR Range	Up to 40 m
Dimensions	92mmx84.8mmx269.6mm (3.62"x3.34"x3.34")
Weight	Approx 900g (1.98lb)

▶ Key Features

1 megapixel high-performance CMOS
Analog HD output, up to 720p resolution
Day/Night switch
DNR
Smart IR
Up to 40 m IR distance
Switchable TVI/AHD/CVI/CVBS
IP66

epcom[®]

Professional Video Surveillance Solutions