

B8TURBOEXIR

Turbo HD EXIR Bullet Camera

epcom®



B8-TURBO-EXIR2W / B8-TURBO-EXIR28W

B8-TURBO-EXIR2 / B8-TURBO-EXIR2

► Camera

Image Sensor	1/3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H) * 1080(V)
Min. Illumination	0.01Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Speed	1/25 (1/30)s to 1/50,000 s
Lens	2.8 mm (B8-TURBO-EXIR28 / B8-TURBO-EXIR28W) 3.6 mm (B8-TURBO-EXIR2 / B8-TURBO-EXIR2 W) Angle of view:103.5° (2.8 mm) 80.9° (3.6 mm)
Lens Mount	M12
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	1080p @ 25 fps / 1080p @ 30 fps
HD Video Output	1 Analog HD output
CVBS Output	1Vp-p Composite Output (75Ω / BNC)
S/N Ratio	More than 52dB

► General

Working Temperature/ Humidity	-40°C-60°C(-40°F-140°F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	Max. 4 W
Weather Proof Ratings	IP66
IR Range	Up to 40 m
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	94.6×83×210.8mm(3.72"×3.27"×8.30")
Weight	700 g (1.54 lbs)

► Menu

Scene	Indoor, outdoor, indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Smart IR/Color/BW
White Balance	Indoor, Outdoor, Manual
Privacy Mask	On/Off, maximum 8 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English
Function	Digital noise reduction and mirror

► Key Features

HD1080p video output
Adopt HDTV Technology
True Day/Night
OSD menu, 3D DNR, Smart IR
EXIR technology, 20/40m IR distance
IP66 weatherproof
Up the Coax (via coaxial cable)

TURBOHD ► series