

LB7TURBOEXIR2 / W

Legend Turbo HD EXIR Bullet Camera



► Camera

Image Sensor	1MP CMOS Image Sensor
Signal System	PAL / NTSC
Effective Pixels	1296(H) * 732(V)
Min. Illumination	0.01Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Speed	1/25 (1/30)s to 1/50,000 s
Lens	Fixed 3.6mm
Lens Mount	M12
Day & Night	ICR
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
Synchronization	Internal synchronization
Video Frame Rate	720p @ 30 fps
HD / CVBS Video	1 Analog HD / CVBS output (selectable)
Output /	1Vp-p Composite Output (75Ω / BNC)
S/N Ratio	More than 62dB

► General

Working Temperature	40°C-60°C (-40°F - 140°F)
Humidity	90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	Max. 4W
Weather Proof Ratings	IP66
IR Range	Up to 40m
Dimensions	86.22 × 82.05 × 220.13 mm (3.39"× 3.23"× 8.67")
Weight	700 g (1.54 lbs)

epcom[®]



LEGEND
TURBOHD